

## Quick Release Couplings: QuickBreak® ISO B



### Technical Specification

- ISO7421-1 Series B
- Sizes 1/8" to 1 (1 1/4" to 2" available to order)
- Materials: Brass, Plated Steel, Stainless Steel 303, 316 available
- Buna, Viton, EPDM & Neoprene seals
- Working pressures up to 300 bar (depending on material & size)
- Double shut-off valve configuration
- Effective ball-locking system
- Special seals are available on request

### Features & Benefits

- Interchangeable with other fittings manufactured to ISO-B standard
- Superior pressure and flow characteristics
- Sleeve lock if required
- Quick, easy and simple to operate

### Applications

- High pressure hydraulic circuits
- Hydraulic pumps, valves quick tool change
- Die casting
- Test benches
- Plastics industry
- Steel industry

Product Code	DIN	Size	Connection	Material
GC-C10-SS	10	3/8"	Coupler	Stainless Steel
GC-C10-BR	10	3/8"	Coupler	Brass
GC-C10-ST	10	3/8"	Coupler	Steel Plated
GC-P10-SS	10	3/8"	Probe	Stainless Steel
GC-P10-BR	10	3/8"	Probe	Brass
GC-P10-ST	10	3/8"	Probe	Plated Steel
GC-C19-SS	19	3/4"	Coupler	Stainless Steel
GC-C19-BR	19	3/4"	Coupler	Brass
GC-C19-ST	19	3/4"	Coupler	Steel Plated
GC-P19-SS	19	3/4"	Probe	Stainless Steel
GC-P19-BR	19	3/4"	Probe	Brass
GC-P19-ST	19	3/4"	Probe	Plated Steel
GC-C06-SS	6	1/4"	Coupler	Stainless Steel



## Quick Release Couplings: QuickBreak<sup>®</sup> ISO B

Product Code	DIN	Size	Connection	Material
GC-C06-BR	6	1/4"	Coupler	Brass
GC-C06-ST	6	1/4"	Coupler	Steel Plated
GC-P06-SS	6	1/4"	Probe	Stainless Steel
GC-P06-BR	6	1/4"	Probe	Brass
GC-P06-ST	6	1/4"	Probe	Plated Steel
GC-C13-SS	13	1/2"	Coupler	Stainless Steel
GC-C13-BR	13	1/2"	Coupler	Brass
GC-C13-ST	13	1/2"	Coupler	Steel Plated
GC-P13-SS	13	1/2"	Probe	Stainless Steel
GC-P13-BR	13	1/2"	Probe	Brass
GC-P13-ST	13	1/2"	Probe	Plated Steel
GC-C25-SS	25	1"	Coupler	Stainless Steel
GC-C25-BR	25	1"	Coupler	Brass
GC-C25-ST	25	1"	Coupler	Steel Plated
GC-P25-SS	25	1"	Probe	Stainless Steel
GC-P25-BR	25	1"	Probe	Brass
GC-P25-ST	25	1"	Probe	Plated Steel

